

# MATERIAL SAFETY DATA SHEET (MSDS)

### NINGBO JINHAI CHENGUANG CHEMICAL CORPORATION

Hydrogenated Hydrocarbon Resin CAS Number: 69430-35-9

SECTION I IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND COMPANY

**PRODUCT NAME:** Haitack<sup>™</sup> JH-6100 / JH-6125 / JH-6130 / JH-6140 / JH-6140P / JH-6200

CHEMICAL FAMILY: Hydrogenated Hydrocarbon Resin

**CAS NUMBER:** 69430-35-9

**RELEVANT USES:** Additive for adhesives, paints, coatings, inks.

MANUFACTURER/SUPPLIER NAME:

NINGBO JINHAI CHENGUANG CHEMICAL CORPORATION.

ADDRESS: No. 2666, Binhai Road, Ningbo Petrochemical and Technological

Development Zone, Zhejiang Province, 315207, P.R. China

WEBSITE: <u>www.jhvest.com</u>.

**TELEPHONE / FAX:** 0086-574-86363456 / 0086-574-86369000

Date prepared: 7 March, 2023

SECTION 2 HAZARDS IDENTIFICATION

GHS Classification: Combustible Dust

**GHS Label Element** 

Signal word: Warning

Hazard statements: If small particles are generated during further processing, handling or by other means,

may form combustible dust concentrations in air.

**Precautionary statements:** Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

**OTHER HAZARDS** 

None known.

## SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

### SUBSTANCES/MIXTURE\_GENERAL INFORMATION:

Chemical name	Concentration	Additional identification	Notes
Hydrogenated Hydrocarbon resin	>99.2%	proprietary	
Additives	<0.8%	not applicable	

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

This substance has workplace exposure limit(s).

PBT: Persistent, bioaccumulative and toxic substance. vPvB: Very persistent and very bioaccumulative substance.



# **Material Safety Data Sheet (MSDS)**

Hydrogenated Hydrocarbon Resin CAS Number: 69430-35-9

SECTION 4 FIRST AID MEASURES

**DESCRIPTION OF FIRST AID MEASURES** 

**INHALATION:** Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist.

**SKIN CONTACT:** Wash with soap and water. Get medical attention if symptoms occur. If burned by contact with

hot materials, cool molten material adhering to skin as quickly as possible with water, and see a

physician for removal of adhering material and treatment of burn. Get medical attention.

**EYE CONTACT:** Any material that contacts the eye should be washed out immediately with water. If easy to do,

remove contact lenses. Get medical attention if symptoms persist. If molten material contacts the eye, immediately flush with plenty of water for at least 15 minutes. Get medical attention

immediately.

**INGESTION:** Seek medical advice.

SECTION 5 FIRE FIGHTING MEASURES

FLASH POINT >270°C

FLAMMABILITY CLASS (OSHA) IIIB

**HAZARDOUS COMBUSTION PRODUCTS:** 

Thermal decomposition products may include toxic oxides of carbon.

**GENERAL FIRE HAZARDS:** 

Material can accumulate static charges which may cause an electrical spark (ignition source).

Use proper bonding and/or grounding procedures.

**EXTINGUISHING MEDIA** 

**SUITABLE:** Carbon dioxide, dry powder, foam, water spray, sand, etc.

**UNSUITABLE:** None known.

**SPECIAL HAZARDS:** Powdered material; may form explosive dust-air mixtures.

**ADVICE FOR FIREFIGHTERS** 

**SPECIAL FIRE FIGHTING PROCEDURES:** Minimize dust generation and accumulation.

SPECIAL PROTECTIVE EQUIPMENT: Self-contained breathing apparatus and full protective clothing must be

worn

SECTION 6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Wear appropriate personal equipment.

**ENVIRONMENTAL PRECAUTIONS:** Not regarded as dangerous for the environment.

METHODS AND MATERIALS FOR CONTAINMENT AND OF CLEANING UP:

Sweep up and place in a clearly labeled container for chemical waste.

**NOTIFICATION PROCEDURES:** In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

**DISPOSAL:** Use authorized discharge or burn in approved installation.

# 金海 Jinhai

# Material Safety Data Sheet (MSDS)

Hydrogenated Hydrocarbon Resin CAS Number: 69430-35-9

### SECTION 7 HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Prevent the inhalation of the dust or vapor of products; wear protective

equipment listed at section 8.

**STORAGE:** Keep at temperature not exceeding 30 °C.

Keep container closed and away from the sun.

**END USE(S):** Adhesives, Modifier, etc.

# SECTION 8 EXPOSURE CONTROLS, PERSONAL PROTECTION

**CONTROL PARAMETERS** 

OCCUPATIONAL EXPOSURE LIMITS: 5 mg/OSHA (respirable dust)

Provide explosion proof ventilation to meet exposure limits

PERSONAL PROTECTIVE EQUIPMENT

**GENERAL INFORMATION:** Eye bath; washing facilities in work place.

**RESPIRATOR:** Atmospheric levels should be maintained below exposure limits; use a

NIOSH-MSHA approved respirator based on contamination levels in the

work place.

**EYE/FACE PROTECTION:** Wear splash-proof or dust resistance safety goggles.

Wear a face shield when working with molten material.

**HAND PROTECTION:** Wear appropriate protective gloves.

OTHER PROTECTIVE EQUIPMENT: Wear rubberized apron to help protect body from spills or molten resin.

WORK/HYGIENIC PRACTICES: Employees before leaving work should wash hands. Keep product away

from food, beverages and tobacco.

#### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

### **APPEARANCE**

PHYSICAL STATE: Solid

FORM: Granules/pellets
COLOR: Water white
ODOR: Odorless

ODOR THRESHOLD: Not determined.pH: No data available.

**SOLUBILITY** 

SOLUBILITY IN WATER: Negligible

**SOLUBILITY (OTHER):** Soluble in toluene, hexane, etc.

INORGANIC SOLVENT: Insoluble

PARTITION COEFFICIENT (N-OCTANOL/WATER): No data available.

**AUTOIGNITION TEMPERATURE:** No data available.

**DECOMPOSITION TEMPERATURE:** Thermal stability not tested. Low stability hazard expected at normal

operating temperatures.

FLASH POINT: >270℃.



# **Material Safety Data Sheet (MSDS)**

Hydrogenated Hydrocarbon Resin CAS Number: 69430-35-9

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES (continued)

**SOFTENING POINT:** 98-145 °C.

BOILING POINT:

EVAPORATION RATE:

Not determined.

No data available.

LIMIT – UPPER (%)--:

No data available.

No data available.

No data available.

VAPOR PRESSURE:

VAPOR DENSITY (AIR=1):

No data available.

No data available.

No data available.

SPECIFIC GRAVITY: 1.05-1.10

**VISCOSITY:** 200~3000 mPa•s (180°C)

**EXPLOSIVE PROPERTIES:** No data available. **OXIDIZING PROPERTIES:** No data available.

SECTION 10 STABILITY AND REACTIVITY

**STABILITY:** Stable under normal storage condition.

**CONDITION TO AVOID:** Open flames, high temperatures.

MATERIAL TO AVOID: Strong oxidizing agents

**HAZARDOUS DECOMPOSITIONOR BY PRODUCTS:** 

Carbon monoxide, carbon dioxide

HAZARDOUS POLYMERIZATION: Will not occur

SECTION 11 TOXICOLOGICAL INFORMATION

**ACUTE TOXICITY** 7g/kg oral-mammal LD50 (LD50 > 2000mg/kg)

**SKIN & EYE CONTACT** Please see section 8.

CARCINOGENICITY Not listed as carcinogen by NTP, OSHA, IARC and ACGIH

SECTION 12 ECOLOGICAL INFORMATION

ENVIRONMENTAL IMPACT None to our knowledge

SECTION13 DISPOSAL CONSIDERATIONS OF THIS PRODUCT

None to our knowledge

SECTION 14 TRANSPORT INFORMATION

Important Note: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Consult your company's Hazardous Materials/Dangerous Goods expert for information specific to your situation.

IMDG/IMO

Not Regulated



# **Material Safety Data Sheet (MSDS)**

Hydrogenated Hydrocarbon Resin CAS Number: 69430-35-9

**SECTION 15 REGULATION INFORMATION** 

Safety, health and environmental regulations/legislation specific for the substance or mixture:

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical List: NONE

**OSHA:** Nonhazardous

**TSCA (US Toxic Substances Control Act):** This product is listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

**ECL (Korean Toxic Substances Control Act):** This product is listed on the Korean inventory or otherwise complies with the Korean Toxic Substances Control Act.

**Inventory of Existing Chemical Substances in China:** All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

**EINECS (EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES):** This product is listed on EINECS or otherwise complies with EINECS Requirements.

MITI (JAPANESE HANDBOOK OF EXISTING AND NEW CHEMICAL SUBSTANCES): All components of this product are listed on the MITI inventory.

### SECTION 16 OTHER INFORMATION

Revision Information: Update MSDS

Key literature references and sources for data: No data available

Training information: No data available.

Issue Date: 7/3/2023

SDS No:

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

PREPARED BY: TECHNOLOGY CENTER OF NINGBO JINHAI CHENGUANG CHEMICAL CORPORATION.